







# TRACK SYSTEM

## FOR AGRICULTURE TRACTOR

-  **TRACTOR POWER**
-  **SOIL PROTECTION**  
Reduced compaction
-  **HIGHER EFFICIENCY**  
Lower fuel consumption

### KEY FEATURES

-  Designed for 90 – 120 HP tractors
-  Simple and robust structure with a three-point mounting system for easy installation
-  Equipped with 2 sets of track rollers for stable operation
-  Reduces ground pressure and improves vehicle passability
-  Increases traction, reduces fuel consumption, protects farmland, and supports sustainable agriculture
-  Equipped with a self-adjusting hydraulic tensioning system







**EKBL-400F**






 Compatible with major global combine brands

### SPECIFICATIONS

ITEM	SPECIFICATION	ITEM	SPECIFICATION
 Model	EKBL-400F / EKBL-635R	 Ground Contact Area	1.12 m <sup>2</sup> / 2.13 m <sup>2</sup>
 Overall Dimensions(L x W x H)	1860 x 550 x 1340 mm 2030 x 700 x 1860 mm	 Mounting Type	Hub Mounting System
 Track Width	400 mm / 635 mm	 Power Requirement	90-120 hp
 Ground Contact Length	1400 mm / 1680 mm	 Track Tensioning System	Hydraulic tensioning system



 [www.agribromfg.com](http://www.agribromfg.com)  
 [alfred@agribromfg.com](mailto:alfred@agribromfg.com)  
 +86 139 6428 6192

Qingdao E-teke Industrial Equipment Co., Ltd

**HIGH TRACTION      LOW SOIL COMPACTION      MAXIMUM PRODUCTIVITY**