

TRACK SYSTEM

FOR COMBINE HARVESTERS



MAX. SPEED
Up to 35 km/h



SOIL PROTECTION
Reduced compaction



HIGHER EFFICIENCY
Lower fuel consumption

KEY FEATURES



Maximum travel speed up to 35 km/h



Simple and robust structure with a three-point mounting system for easy installation



Equipped with 4 sets of track rollers for stable operation



Suitable for models 137 – 197 hp



Ideal for wet environments such as rice paddies and marshlands



Equipped with a self-adjusting hydraulic tensioning system

EKBL-635A



JOHN DEERE

C230 / 3518 / 3316



4088 / 4099



Compatible with major global combine brands

SPECIFICATIONS

ITEM	SPECIFICATION	ITEM	SPECIFICATION
Model	EKBL-635A	Ground Contact Area	2.67 m ²
Overall Dimensions(L x W x H)	2580 x 698 x 1345 mm	Mounting Type	Hub mounting(wheel hub connection)
Track Width	635 mm	Power Requirement	102~147 kw
Ground Contact Length	2100 mm	Track Tensioning System	Hydraulic tensioning system



www.agribromfg.com
alfred@agribromfg.com
 +86 139 6428 6192

Qingdao E-teke Industrial Equipment Co., Ltd

HIGH TRACTION

LOW SOIL COMPACTION

MAXIMUM PRODUCTIVITY