

# TRACK SYSTEM

## FOR AGRICULTURE TRACTOR



**MAX. SPEED**  
35 km/h



**SOIL PROTECTION**  
Reduced compaction



**HIGHER EFFICIENCY**  
Lower fuel consumption

### KEY FEATURES



Designed for 300 HP + tractors



Simple and robust structure with a mounting system for easy installation



Equipped with 2 sets of track rollers for stable operation



Reduces ground pressure and improves vehicle passability



Increases traction, reduces fuel consumption, protects farmland, and supports sustainable agriculture



Equipped with a self-adjusting hydraulic tensioning system



**EKBL-915TR**  
(Rear)



(Front)

**EKBL-762TF**



**JOHN DEERE**

3004



3154



Compatible with major global combine brands

### SPECIFICATIONS

| ITEM                          | SPECIFICATION                               | ITEM                    | SPECIFICATION                             |
|-------------------------------|---|-------------------------|---|
| Model                         | EKBL-762TF / EKBL-915TR                     | Ground Contact Area     | 2.45 m <sup>2</sup> / 2.64 m <sup>2</sup> |
| Overall Dimensions(L x W x H) | 2380 x 762 x 1430mm<br>2228 x 915 x 1766 mm | Mounting Type           | Hub Mounting System                       |
| Track Width                   | 762 mm / 915 mm                             | Power Requirement       | ≥ 300 hp                                  |
| Ground Contact Length         | 1610 mm / 1444 mm                           | Track Tensioning System | Hydraulic tensioning system               |



www.agribromfg.com



alfred@agribromfg.com



+86 139 6428 6192

Qingdao E-teke Industrial Equipment Co., Ltd

HIGH TRACTION

LOW SOIL COMPACTION

MAXIMUM PRODUCTIVITY