

# TRACK SYSTEM

## FOR COMBINE HARVESTERS



**MAX. SPEED**  
Up to 35 km/h



**SOIL PROTECTION**  
Reduced compaction



**HIGHER EFFICIENCY**  
Lower fuel consumption

### KEY FEATURES



Multi-tooth rubber semi-track system, designed to reduce drive power loss and extend track service life



Simple and robust structure with a three-point mounting system for easy installation



Equipped with 4 sets of track rollers for stable operation



Suitable for models above 300hp



Features pitch and swing design, improves mobility, and performs well in harsh working conditions.



Equipped with a self-adjusting hydraulic tensioning system

## EKBL-915E



**JOHN DEERE**

660 / 670 / 680 / 760 / 770



6130 / 6140 / 6088 / 7130



Compatible with major global combine brands

### SPECIFICATIONS

ITEM	SPECIFICATION	ITEM	SPECIFICATION
Model	EKBL-915E	Ground Contact Area	3.84 m <sup>2</sup>
Overall Dimensions(L x W x H)	2939 x 915 x 1570 mm	Mounting Type	Hub mounting(wheel hub connection)
Track Width	915 mm	Power Requirement	≥230 kw
Ground Contact Length	1900 mm	Track Tensioning System	Hydraulic tensioning system



[www.agribromfg.com](http://www.agribromfg.com)  
[alfred@agribromfg.com](mailto:alfred@agribromfg.com)  
 +86 139 6428 6192

Qingdao E-teke Industrial Equipment Co., Ltd

HIGH TRACTION

LOW SOIL COMPACTION

MAXIMUM PRODUCTIVITY