

# TRACK SYSTEM

## FOR FORAGE HARVESTERS

- 
**TRACTOR POWER**  
 ≥ 200 kw
- 
**SOIL PROTECTION**  
 Reduced compaction
- 
**HIGHER EFFICIENCY**  
 Lower fuel consumption





### KEY FEATURES

- 
 Simple structure, easy to install
- 
 Suitable for muddy, waterlogged, uneven, and rainy field conditions with strong anti-stuck performance
- 
 Can directly follow tractors or harvesters into the field for operation
- 
 Reduces intermediate transfer steps from harvester → temporary storage point → wheeled transport vehicles
- 
 Significantly improves overall operational efficiency
- 
 Equipped with a self-adjusting hydraulic tensioning system




**EKG-890**



### SPECIFICATIONS

ITEM	SPECIFICATION	ITEM	SPECIFICATION
 Model	EKG-890	 Ground Contact Area	3.26 m <sup>2</sup>
 Overall Dimensions(L x W x H)	2980 x 890 x 1150 mm	 Mounting Type	Hub mounting(wheel hub connection)
 Track Width	890 mm	 Power Requirement	≥ 200 kw
 Ground Contact Length	1832 mm	 Track Tensioning System	Hydraulic tensioning system



 [www.agribromfg.com](http://www.agribromfg.com)  
 [alfred@agribromfg.com](mailto:alfred@agribromfg.com)  
 +86 139 6428 6192

Qingdao E-teke Industrial Equipment Co., Ltd

HIGH TRACTION

LOW SOIL COMPACTION

MAXIMUM PRODUCTIVITY