

# TRACK SYSTEM

## FOR FORAGE HARVESTERS



- TRACTOR POWER**  
≥ 230 kw
- SOIL PROTECTION**  
Reduced compaction
- HIGHER EFFICIENCY**  
Lower fuel consumption

### KEY FEATURES

- Max. speed is 35 km/h
- Suitable for muddy, waterlogged, uneven, and rainy field conditions with strong anti-stuck performance
- Can directly follow tractors or harvesters into the field for operation
- Reduces intermediate transfer steps from harvester → temporary storage point → wheeled transport vehicles
- Significantly improves overall operational efficiency
- Equipped with a self-adjusting hydraulic tensioning system

**EKPH-890-2**



Compatible with major global combine brands

### SPECIFICATIONS

ITEM	SPECIFICATION	ITEM	SPECIFICATION
Model	EKPH-890-2	Ground Contact Area	3.26 m <sup>2</sup>
Overall Dimensions(L x W x H)	3027 x 890 x 1186mm	Mounting Type	Hub mounting(wheel hub connection)
Track Width	890 mm	Power Requirement	≥ 230 kw
Ground Contact Length	1833 mm	Track Tensioning System	Hydraulic tensioning system



**HIGH TRACTION**      **LOW SOIL COMPACTION**      **MAXIMUM PRODUCTIVITY**

[www.agribromfg.com](http://www.agribromfg.com)  
[alfred@agribromfg.com](mailto:alfred@agribromfg.com)  
 +86 139 6428 6192